



DISPERTEC UNIVERSAL White Glue (General use)

ISO 9001
BUREAU VERITAS
Certification



COD.FICHA:	FT-220016-I
Nº EDICIÓN:	01
Nº REVISIÓN:	01
FECHA VIGOR:	14/09/2011

Description and applications:

DISPERTEC UNIVERSAL is a General use water-based dispersion adhesive D-2 , special for wood. It can be used in:

- Furniture
- Chairs manufacture
- Stratified boards
- General woodworks
- DIY

Technical data:

Composition:	Vinyllic polymers.
Packaging:	1Kg bottles, 14 and 32 Kg PE drums, and 1.300 Kg containers.
Appearance:	Dense liquid.
Colour:	<i>Dispersion:</i> White / <i>Film:</i> Translucent

Properties:	Value:	Unity:	Standard:
Brookfield Viscosity: (23°C, R6-20 rpm)	15.000 – 20.000	mPa·s	UNE-53-307
pH (20°C):	5,0 – 8,0	---	DIN-53785
Density (23°C):	1,35	g/cm ³	UNE-EN 542
Open time (20°C):	10 - 30	Min.	I.M.
MTTF:	5 - 7	°C	DIN-53787

Source: Laboratory tests.

Characteristics:

- Long open time.
- Good final adhesion.
- Suitable for different porous wood materials.
- For general use.

Instructions for use:

Surfaces to join have to be free of dust, oil, grease, etc.

Stir the product before use.

Apply a thin layer of adhesive on one of the surfaces and put both parts under pressure. Drying and pressing time vary depending on the environmental conditions.

Security and hygiene:

For further information, please request safety data sheet.

Storage:

DISPERTEC MX-6331 can be stored at normal temperatures (approx. 20°C) for approx. 12 months.

Keep away from sunlight and protect from frost. Temperatures higher than 30°C should be avoided. The product is sensitive to frost and must not be stored at temperatures below 5°C. Frozen product is irreversibly damaged.

Cleaning:

Fresh product: Application tools and equipment can be cleaned with water.

Cured product: Mechanical means.

Note:

The technical information provided by QS ADHESIVES & SEALANTS, S.L., either verbally or in writing is based on our present knowledge and is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved.

The user is obliged to ensure that our products are suitable for the process and the use in question.

In any case our liability is limited to the value of goods supplied by us and used by you. We provide products with consistent quality, according to our general conditions of sale and distribution